



Door Access Control

C3-100



Specification

Number of Door : 1 Door
Card Holders Capacity : 30,000
Log Events Capacity : 100,000
Communication : TCP/IP and RS-485
Number of Readers Supported : 2 (26-bit wiegand reader)
Types of Readers Supported : 26-bit Wiegand,
others upon request
Number of Inputs :2(1 Exit Button, 1 Door Sensor)
Number of Outputs : 2 (1-From C Relay for
Lock and 1-Form C Relay for Aux Output)
Weight : 7.4lbs (3.35kg)
Enclosure : Powder Coated Aluminium
Mounting : Wall Mount
Recommended Power Supply : 12V DC, 1.5A
Dimensions (Bundle Only) : 380mm(L)X80mm(W)
X 280mm(H)
Dimensions (Board Only) : (160mm×106mm)

Features:

- ▶ TCP/IP and RS485 communication
- ▶ Built-in Auxiliary input and Output
- ▶ Access Control Functions
- ▶ Support full range of card readers

Software and Database Supported :

Access Security System 3.5 (Desktop Version)
Database Type:- MS Access / MS SQL

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase.
Actual product may differ slightly to that depicted for ongoing product development