



# Heavy Duty Automatic Tripod Turnstile

## ETA-2000A

### Specification

Passage Width : =550mm  
Throughput rate : 35p/m  
Power Supply : 100 ~240V  
Operational Voltage : 24V  
Max tolerance of Arms : 80 Kg  
Angle per rotation : 120 0  
Operation Type : Oneway - Bidirectional  
Flow Rate : 25-48 passages/minute  
Input control signal : Dry contact  
Max Power Consumption : 30 W  
Frequency : 50~60hz  
Protection Level : IP 54  
Working Temperature : -25 ~ +70OC  
Electro - magnetic Drive : DC  
Dimension Excluding Bar : 1200x280x980 mm  
Net Weight Including Bar : 52kg  
Opening Duration : 5s - 60s

#### Features:

##### Controller

- ▶ Full-Auto mode
- ▶ Single or Bi-directional function in mechanical and electrical versions

- ▶ Automatic reset of barrier arms after each passage
- ▶ Adjustable time out delay
- ▶ Operating Mode
  - ▶ Single passage in the set direction
  - ▶ Bi-directional passage
  - ▶ Free passage in the set direction
  - ▶ Always free or locked

#### Materials

- ▶ Housing : Made in metal sheet and painted, in or stainless steel AISI 304 or AISI 316
- ▶ Barrier Arms : Stainless steel
- ▶ Lid (Optional) : Stainless steel or artificial stone (black / brown)

#### Colours & Finishes

- ▶ High quality powder coating plus lacquered finish
- ▶ Dark grey color high quality powder coating plus lacquered finish
- ▶ Sandpaper powder coating with pearl mica effect

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development