



# Full Height Turnstile - Single Door

## FHT-TL-149



### Specification

Power Supply : 100V ~ 240V AC  
Control Circuit : 24 V DC  
Power Consumption : 30W  
Operating Temperature : -25°C ~ +70°C  
Protection level (IP) :  $\geq 44$  | Humidity : 95%  
MCBF : 5 Million Cycles  
Hydraulic damper : Adjustable  
Solenoid : 24V DC 100%  
Throughput : Person  
Signal Output : 12V Pulse  
Communication Interface : RS485 or TCP IP  
Passage width :  $\leq 650$ mm  
Frequency :  $\leq 50$ Hz or 60Hz  
Electro-magnetic drive : DC  
Section version : 90 degree  
No of arms : 4 arms  
Dimensions : 1630 x 1500 x 2310 mm  
Net weight : 220 kg

### Feature:

- ▶ Designed for secure operation with aesthetics in mind
- ▶ Corrosion protected S/S frame
- ▶ Minimal exposed hardware
- ▶ Heavy Gauge materials ASTM Standard
- ▶ Consists of rotor assembly, shield
- ▶ Assembly, barrier section, mechanism housing & ceiling plate
- ▶ The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- ▶ Single passage in the set direction
- ▶ Bi-directional single passage
- ▶ Free passage in the direction
- ▶ Always free or locked

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development