



## Integrated with Fingerprint Recognition and RFID card Technology

### ML10-ID



### Specification

Material : Zinc Alloy

Front : 69(W)×155(L)×35(D)mm

Back : 69(W)×155(L)×25(D)mm

User Capacity : 90

Admin : 20

Normal User : 120

Temporary User : 40

Operating Temperature : - 20°C - 55°C

Power input : 4 x AA alkaline Battery

Backup unlock mechanism :

Mechanical Key & 9V Battery

Standard : 39 to 46mm | 47 to 54mm

Optional : 30 to 38mm | 55 to 60mm

- ▶ Three independent unlock method: Fingerprint, ID-Tag, mechanical key
- ▶ User capacity: 180
- ▶ Fingerprint capacity: 90
- ▶ Card capacity: 90
- ▶ With the new generation fingerprint recognition algorithm
- ▶ Rugged, sleek and compact design
- ▶ American standard single latch for easy replacement and installation
- ▶ Independent clutch motor design under patent protection
- ▶ Idle handle design to prevent from forcible entry
- ▶ Registration data are stored even if there is power loss
- ▶ Handle, latch and strike is reversible design for all door open direction

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development